







TTDM	TTSIM-1	TTSIM-1A	TTA-SIM-1A	TTSIM-2	TTA-SIM-2		
							
+ max. 127 SIM	nur mit TTDM						Stand alone
1.500 m	1.500 m	150 m	150 m	150 m	150 m	TT-1000	Sensoren Sensorleitungen mischbar bis zur max. Länge von
1=10m Sensortg.	1=10m Sensortg.	1=10m Sensortg.	1=10m Sensortg.	1=10m Sensortg.	1=10m Sensortg.	TT-MINI	
1.500 m	1.500 m	150 m	150 m	150 m	150 m	TT-3000	
1.500 m	1.500 m	150 m	150 m	150 m	150 m	TT-5000	
1.500 m	1.500 m	150 m	150 m	150 m	150 m	TT-5001	
6 + Sensortg.	6 + Sensortg.	6 + Sensortg.	6 + Sensortg.	6 + Sensortg.	6 + Sensortg.	TT-FFS	
						12 V DC	Spannung
						24 V AC	
						24 V DC	
						120 V AC	
						230 V AC	
Aufputz	TS 35	TS 35	Aufputz	TS 35	Aufputz	Montageart	Gehäuse
IP 54			IP 20		IP 20	Schutzart	
300x240x85	70x85x65	70x86x58	240x120x110	70x86x58	240x120x110	Maße BxHxT [mm]	
						Ortungsanzeige	Funktionen
						Akust. Alarm	
abschaltbar	abschaltbar	abschaltbar	abschaltbar	abschaltbar	abschaltbar	Auto-Reset	
> 2.000 Ereignisse						Logbuch	
						Netz zu TTDM	Netzwerke
RS-232/RS-485	RS-232	RS-232	RS-232	RS-232	RS-232	Modbus	
RS-232/RS-485	RS-232	RS-232	RS-232	RS-232	RS-232	OptoMux	
RS-232/RS-485	RS-232	RS-232	RS-232	RS-232	RS-232	JC Metasys	
max. 32 SIM	max. 32 SIM	max. 32 SIM	max. 32 SIM	max. 32 SIM	max. 32 SIM	Ethernet / Web	Ausgänge
2 W / 5A		1 W / 2A	1 W / 2A	1 W / 2A	1 W / 2A	Leckage (*)	
2 W / 5A		(1) W / 2A	(1) W / 2A	(1) W / 2A	(1) W / 2A	Störung (*)	
2 W / 5A		(1) W / 2A	(1) W / 2A	(1) W / 2A	(1) W / 2A	Wartung (*) (**)	
						opt. 4-20mA	